

	SAFETY DATA SHEET	Page : 1 / 15
		Revision nr : 1.0
		Issue date : 16/06/2021
	ANYCUBIC 3D Printing UV Sensitive Resin	Supersedes :

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : ANYCUBIC
3D Printing UV Sensitive Resin

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Consumer use
Use of the substance/mixture : 3D printer filaments

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Shenzhen Anycubic Technology Co., Ltd
Room 101-501, Building No. 11, Yinhe Industrial Park, Yinhe Community, Yuanshan Street
518000 Longgang District, Shenzhen, Guangdong - China
T 15002066159
xiexiaona@anycubic.com

1.4. Emergency telephone number

Emergency number : 15112413757
Only available during office hours.

Country	Official advisory body	Address	Emergency number
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals-24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)
United Kingdom	National Poisons Information Service (Newcastle Centre) Regional Drugs and Therapeutics Centre, Wolfson Unit	Claremont Place Newcastle-upon-Tyne NE1 4LP Newcastle	0844 892 0111 (UK only, 24/7, healthcare professionals only)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin Irrit. 2 H315
Eye Irrit. 2 H319
Skin Sens. 1 H317
STOT SE 3 H335
Aquatic Chronic 2 H411


Full text of H-statements: see section 16

	SAFETY DATA SHEET	Page : 2 / 15
		Revision nr : 1.0
		Issue date : 16/06/2021
	ANYCUBIC 3D Printing UV Sensitive Resin	Supersedes :

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word : Warning

Hazardous ingredients : Epoxy resins; (1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate

Hazard statements (CLP) : H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H335 - May cause respiratory irritation.
H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP) : P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.
P261 - Avoid breathing vapours.
P264 - Wash hands thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.
P280 - Wear protective gloves, protective clothing, eye protection, face protection.
P302+P352 - IF ON SKIN: Wash with plenty of water.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P391 - Collect spillage.
P501 - Dispose of contents and container to an approved waste disposal plant.

2.3. Other hazards

Other hazards : Results of PBT and vPvB assessment : Not applicable.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

	SAFETY DATA SHEET	Page : 3 / 15
		Revision nr : 1.0
		Issue date : 16/06/2021
	ANYCUBIC 3D Printing UV Sensitive Resin	Supersedes :

Substance name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Epoxy resins	(CAS-No.) 61788-97-4 (EC-No.) 612-377-4	60	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate	(CAS-No.) 42978-66-5 (EC-No.) 256-032-2 (EC Index) 607-249-00-X	35	Eye Irrit. 2, H319 STOT SE 3, H335 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411
hydroxycyclohexyl phenyl ketone	(CAS-No.) 947-19-3 (EC-No.) 213-426-9	5	Not classified

Specific concentration limits:

Substance name	Product identifier	Specific concentration limits
(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate	(CAS-No.) 42978-66-5 (EC-No.) 256-032-2 (EC Index) 607-249-00-X	(10 ≤C < 100) STOT SE 3, H335

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

Additional advice	: First aider: Pay attention to self-protection!. Concerning personal protective equipment to use, see section 8. Never give anything by mouth to an unconscious person. In case of doubt or persistent symptoms, consult always a physician. Show this safety data sheet to the doctor in attendance.
Inhalation	: Remove casualty to fresh air and keep warm and at rest. Give oxygen or artificial respiration if necessary. In case of doubt or persistent symptoms, consult always a physician.
Skin contact	: Remove contaminated clothing and shoes. Gently wash with plenty of soap and water. In case of doubt or persistent symptoms, consult always a physician.
Eyes contact	: Rinse immediately carefully and thoroughly with eye-bath or water. Remove contact lenses, if present and easy to do. Continue rinsing. In case of doubt or persistent symptoms, consult always a physician.
Ingestion	: Rinse mouth thoroughly with water. Do not induce vomiting. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	: May cause respiratory irritation. The following symptoms may occur: Headache. Nausea. Irritation.
Skin contact	: May cause an allergic skin reaction. Causes skin irritation. The following symptoms may occur: Redness, pain.
Eyes contact	: Causes serious eye irritation. The following symptoms may occur: Redness, pain.
Ingestion	: May cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

	SAFETY DATA SHEET	Page : 4 / 15
		Revision nr : 1.0
		Issue date : 16/06/2021
	ANYCUBIC 3D Printing UV Sensitive Resin	Supersedes :

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : carbon dioxide (CO₂), powder, alcohol-resistant foam, water spray.
- Unsuitable extinguishing media : Strong water jet.

5.2. Special hazards arising from the substance or mixture

- Specific hazards : Combustible. Heating will cause a rise in pressure with a risk of bursting. Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours. Can form explosive mixture with air.
- Hazardous decomposition products in case of fire : Carbon oxides (CO, CO₂). Toxic fumes may be released.

5.3. Advice for firefighters

- Firefighting instructions : Evacuate area. Use water spray or fog for cooling exposed containers. Contain the extinguishing fluids by bunding. Prevent fire fighting water from entering the environment.
- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus.
- Other information : Do not allow run-off from fire-fighting to enter drains or water courses. Dispose of waste in accordance with environmental legislation.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- For non-emergency personnel : Evacuate unnecessary personnel. Keep upwind. Provide adequate ventilation. Do not breathe vapours. Avoid contact with skin, eyes and clothing. Wear recommended personal protective equipment. Concerning personal protective equipment to use, see section 8. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ensure equipment is adequately earthed. Use explosion-proof equipment. Use only non-sparking tools.

6.1.2. For emergency responders

- For emergency responders : Ensure procedures and training for emergency decontamination and disposal are in place. Concerning personal protective equipment to use, see section 8.

6.2. Environmental precautions

- Do not allow to enter into surface water or drains. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Stop leak if safe to do so. Dam up the liquid spill. Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. Recover large spills by pumping (use an explosion proof or hand pump). Place in a suitable container for disposal in accordance with the waste regulations (see Section 13). This material and its container must be disposed of in a safe way, and as per local legislation.

6.4. Reference to other sections

- Concerning personal protective equipment to use, see section 8. Concerning disposal elimination after cleaning, see section 13.

	SAFETY DATA SHEET	Page : 5 / 15
		Revision nr : 1.0
		Issue date : 16/06/2021
	ANYCUBIC 3D Printing UV Sensitive Resin	Supersedes :

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Provide adequate ventilation. Do not breathe vapours. Avoid contact with skin, eyes and clothing. Use personal protective equipment as required. Concerning personal protective equipment to use, see section 8. Take any precaution to avoid mixing with Incompatible materials, Refer to Section 10 on Incompatible Materials. Ensure proper process control to avoid excess waste discharge (temperature, concentration, pH, time). Avoid release to the environment. Contaminated work clothing must not be allowed out of the workplace. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use explosion-proof equipment. Use only non-sparking tools.

Hygiene measures : Keep good industrial hygiene. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke when using this product. Keep away from food, drink and animal feedingstuffs. Remove contaminated clothes. Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep out of the reach of children.

Storage conditions : Store in a dry, cool and well-ventilated place. Do not store near or with any of the incompatible materials listed in section 10. Bund storage facilities to prevent soil and water pollution in the event of spillage. Take precautionary measures against static discharge.

Heat and ignition sources : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect from sunlight.

Special rules on packaging : Containers which are opened should be properly resealed and kept upright to prevent leakage. Keep container tight closed.

Packaging materials : Keep only in the original container.

7.3. Specific end use(s)

3D printer filaments.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Epoxy resins (61788-97-4)		
Bulgaria	OEL TWA	0,5 mg/m ³ (solid)
Czech Republic	PEL (OEL TWA)	2 mg/m ³ (dust)

Additional information : Recommended monitoring procedures :. Personal air monitoring. Room air monitoring

8.2. Exposure controls

Engineering measure(s) : Organisational measures to prevent /limit releases, dispersion and exposure. See Section 7 for information on safe handling. Use only outdoors or in a well-ventilated area. Take precautionary measures against static discharges. Ensure equipment is adequately earthed.

Personal protective equipment : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

	SAFETY DATA SHEET	Page : 6 / 15
		Revision nr : 1.0
		Issue date : 16/06/2021
	ANYCUBIC 3D Printing UV Sensitive Resin	Supersedes :

Hand protection	: Wear chemically resistant gloves (tested to EN374) . Suitable material: Butyl rubber. Thickness : Not determined. Breakthrough time : Not determined. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.
Eye protection	: Use suitable eye protection (EN166): goggles
Body protection	: Wear suitable protective clothing
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment. Half-face mask (DIN EN 140). full face mask (DIN EN 136). Filter type: (ABEK) (EN14387). The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used. (EN 137)
Thermal hazard protection	: Not required for normal conditions of use. Use dedicated equipment.
Environmental exposure controls	: Avoid release to the environment. Comply with applicable Community environmental protection legislation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: Transparent. clear.
Odour	: odourless.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting / freezing point	: No data available
Freezing point	: No data available
Initial boiling point and boiling range	: 238 °C
Flash point	: 90 °C
Auto-ignition temperature	: 252 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable, liquid
Vapour pressure	: No data available
Vapour density	: No data available
Relative density	: No data available
Density	: 0,8 – 0,9 g/cm ³
Solubility	: Insoluble in water. Soluble in alcohols.
Partition coefficient n-octanol/water	: No data available
Kinematic viscosity	: 1,54 mm ² /s
Dynamic viscosity	: No data available
Explosive properties	: Not applicable. The study does not need to be conducted because there are no chemical groups associated with explosive properties present in the molecule.
Oxidising properties	: Not applicable. The classification procedure needs not to be applied because there are no chemical groups present in the molecule which are associated with oxidising properties.

	SAFETY DATA SHEET	Page : 7 / 15
		Revision nr : 1.0
		Issue date : 16/06/2021
	ANYCUBIC 3D Printing UV Sensitive Resin	Supersedes :

Explosive limits	: No data available
Particle size	: Not applicable
Particle size distribution	: Not applicable
Particle shape	: Not applicable
Particle aspect ratio	: Not applicable
Particle aggregation state	: Not applicable
Particle agglomeration state	: Not applicable
Particle specific surface area	: Not applicable
Particle dustiness	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Combustible. Reference to other sections: 10.4 & 10.5.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect from sunlight. Take precautionary measures against static discharge. See Section 7 for information on safe handling.

10.5. Incompatible materials

Strong oxidizing agents. Acids. Bases. See Section 7 for information on safe handling.

10.6. Hazardous decomposition products

Reference to other sections 5.2.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity : Not classified (Based on available data, the classification criteria are not met)

(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate (42978-66-5)	
LD50/oral/rat	3000 - 8100 mg/kg
LD50/dermal/rabbit	> 2000 mg/kg
hydroxycyclohexyl phenyl ketone (947-19-3)	
LD50/dermal/rat	> 5000 mg/kg
LC50/inhalation/4h/rat	> 1000 mg/m ³ (Exposure time: 4 h)

	SAFETY DATA SHEET	Page : 8 / 15
		Revision nr : 1.0
		Issue date : 16/06/2021
	ANYCUBIC 3D Printing UV Sensitive Resin	Supersedes :

Skin corrosion/irritation	: Causes skin irritation. pH: No data available
Serious eye damage/irritation	: Causes serious eye irritation. pH: No data available
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure	: May cause respiratory irritation.
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)

ANYCUBIC 3D Printing UV Sensitive Resin	
Kinematic viscosity	1,54 mm ² /s

Other information	: Symptoms related to the physical, chemical and toxicological characteristics. For further information see section 4.
-------------------	---------------------------------------------------------------------------------------------------------------------------

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties	: Not applicable
------------------------------------------------------------------	------------------

11.2.2 Other information

Other information	: Symptoms related to the physical, chemical and toxicological characteristics, For further information see section 4
-------------------	-----------------------------------------------------------------------------------------------------------------------

SECTION 12: Ecological information

12.1. Toxicity

Environmental properties	: Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Toxic to aquatic life with long lasting effects.

(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate (42978-66-5)	
LC50 - Fish [1]	4,5 - 10 mg/l (Leuciscus idus)
EC50 - Crustacea [1]	88,7 mg/l (Daphnia Magna)
EC50 72h - Algae [1]	> 28 mg/l (Species: Desmodesmus subspicatus)

hydroxycyclohexyl phenyl ketone (947-19-3)	
LC50 - Fish [1]	24 mg/l (Exposure time: 96 h - Species: Danio rerio [static])

	SAFETY DATA SHEET	Page : 9 / 15
		Revision nr : 1.0
		Issue date : 16/06/2021
	ANYCUBIC 3D Printing UV Sensitive Resin	Supersedes :

12.2. Persistence and degradability

ANYCUBIC 3D Printing UV Sensitive Resin	
Persistence and degradability	No additional information available.

12.3. Bioaccumulative potential

ANYCUBIC 3D Printing UV Sensitive Resin	
Partition coefficient n-octanol/water	No data available
Bioaccumulative potential	No additional information available.

(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate (42978-66-5)	
BCF - Fish [1]	(no significant bioaccumulation expected)
Partition coefficient n-octanol/water	2,77

12.4. Mobility in soil

ANYCUBIC 3D Printing UV Sensitive Resin	
Mobility in soil	No data available

12.5. Results of PBT and vPvB assessment

ANYCUBIC 3D Printing UV Sensitive Resin	
Results of PBT assessment	Not applicable

12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties : Not applicable

12.7. Other adverse effects

Other adverse effects : No data available

SECTION 13: Disposal considerations






13.1. Waste treatment methods

- Product/Packaging disposal recommendations : Avoid release to the environment. Dispose of empty containers and wastes safely. See Section 7 for information on safe handling. Refer to manufacturer/supplier for information on recovery/recycling. Recycling is preferred to disposal or incineration. If recycling is not possible, eliminate in accordance with local valid waste disposal regulations. Handle contaminated packages in the same way as the substance itself. Dispose of contaminated materials in accordance with current regulations. Do not pierce or burn, even after use. Never use pressure to empty container.
- European waste catalogue (2001/573/EC, 75/442/EEC, 91/689/EEC) : This material and its container must be disposed of as hazardous waste. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

	SAFETY DATA SHEET	Page : 10 / 15
		Revision nr : 1.0
		Issue date : 16/06/2021
	ANYCUBIC 3D Printing UV Sensitive Resin	Supersedes :

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
3082	3082	3082	3082	3082
14.2. UN proper shipping name				
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resins ; (1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resins ; (1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate)	Environmentally hazardous substance, liquid, n.o.s. (Epoxy resins ; (1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resins ; (1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resins ; (1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate)
Transport document description				
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resins ; (1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate), 9, III, (-)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resins ; (1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate), 9, III, MARINE POLLUTANT	UN 3082 Environmentally hazardous substance, liquid, n.o.s. (Epoxy resins ; (1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resins ; (1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resins ; (1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate), 9, III
14.3. Transport hazard class(es)				
9	9	9	9	9
				
14.4. Packing group				
III	III	III	III	III
14.5. Environmental hazards				
Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes
No supplementary information available				

14.6. Special precautions for user

Special precautions for user : No data available

- Overland transport

Classification code (ADR) : M6
Special provisions : 274, 335, 375, 601
Limited quantities (ADR) : 5I
Excepted quantities (ADR) : E1
Packing instructions (ADR) : P001, IBC03, LP01, R001
Special packing provisions (ADR) : PP1
Mixed packing provisions (ADR) : MP19

	SAFETY DATA SHEET	Page : 11 / 15
		Revision nr : 1.0
		Issue date : 16/06/2021
	ANYCUBIC 3D Printing UV Sensitive Resin	Supersedes :

Portable tank and bulk container instructions (ADR) : T4
 Portable tank and bulk container special provisions (ADR) : TP1, TP29
 Tank code (ADR) : LGBV
 Vehicle for tank carriage : AT
 Transport category (ADR) : 3
 Special provisions for carriage - Packages (ADR) : V12
 Special provisions for carriage - Loading, unloading and handling (ADR) : CV13
 Hazard identification number (Kemler No.) : 90
 Orange plates :



Tunnel restriction code : -
 EAC code : •3Z

- Transport by sea

Special provisions (IMDG) : 274, 335, 969
 Limited quantities (IMDG) : 5 L
 Excepted quantities (IMDG) : E1
 Packing instructions (IMDG) : LP01, P001
 Special packing provisions (IMDG) : PP1
 IBC packing instructions (IMDG) : IBC03
 Tank instructions (IMDG) : T4
 Tank special provisions (IMDG) : TP1, TP29
 EmS-No. (Fire) : F-A
 EmS-No. (Spillage) : S-F
 Stowage category (IMDG) : A

- Air transport

PCA Excepted quantities (IATA) : E1
 PCA Limited quantities (IATA) : Y964
 PCA limited quantity max net quantity (IATA) : 30kgG
 PCA packing instructions (IATA) : 964
 PCA max net quantity (IATA) : 450L
 CAO packing instructions (IATA) : 964
 CAO max net quantity (IATA) : 450L
 Special provisions (IATA) : A97, A158, A197, A215
 ERG code (IATA) : 9L

- Inland waterway transport

Classification code (ADN) : M6
 Special provisions (ADN) : 274, 335, 375, 601

	SAFETY DATA SHEET	Page : 12 / 15
		Revision nr : 1.0
		Issue date : 16/06/2021
	ANYCUBIC 3D Printing UV Sensitive Resin	Supersedes :

Limited quantities (ADN) : 5 L
 Excepted quantities (ADN) : E1
 Equipment required (ADN) : PP
 Number of blue cones/lights (ADN) : 0

- Rail transport

Classification code (RID) : M6
 Special provisions (RID) : 274, 335, 375, 601
 Limited quantities (RID) : 5L
 Excepted quantities (RID) : E1
 Packing instructions (RID) : P001, IBC03, LP01, R001
 Special packing provisions (RID) : PP1
 Mixed packing provisions (RID) : MP19
 Portable tank and bulk container instructions (RID) : T4
 Portable tank and bulk container special provisions (RID) : TP1, TP29
 Tank codes for RID tanks (RID) : LGBV
 Transport category (RID) : 3
 Special provisions for carriage – Packages (RID) : W12
 Special provisions for carriage - Loading, unloading and handling (RID) : CW13, CW31
 Colis express (express parcels) (RID) : CE8
 Hazard identification number (RID) : 90

14.7. Maritime transport in bulk according to IMO instruments

Code: IBC : No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

3(b) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	ANYCUBIC 3D Printing UV Sensitive Resin ; (1-methyl-1,2-ethanediyl)bis[oxymethyl-2,1-ethanediyl)] diacrylate
3(c) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1	ANYCUBIC 3D Printing UV Sensitive Resin ; (1-methyl-1,2-ethanediyl)bis[oxymethyl-2,1-ethanediyl)] diacrylate

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

15.1.2. National regulations

France

	SAFETY DATA SHEET	Page : 13 / 15
		Revision nr : 1.0
		Issue date : 16/06/2021
	ANYCUBIC 3D Printing UV Sensitive Resin	Supersedes :

No ICPE	Installations classées Désignation de la rubrique	Code Régime	Rayon
4511.text	Dangereux pour l'environnement aquatique de catégorie chronique 2.		
4511.1	La quantité totale susceptible d'être présente dans l'installation étant : 1. Supérieure ou égale à 200 t Quantité seuil bas au sens de l'article R. 511-10 : 200 t. Quantité seuil haut au sens de l'article R. 511-10 : 500 t.	A	1
4511.2	La quantité totale susceptible d'être présente dans l'installation étant : 2. Supérieure ou égale à 100 t mais inférieure à 200 t Quantité seuil bas au sens de l'article R. 511-10 : 200 t. Quantité seuil haut au sens de l'article R. 511-10 : 500 t.	DC	

Germany

Regulatory reference : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1)

German storage class (LGK) : LGK 10 - Combustible liquids

Hazardous Incident Ordinance (12. BlmSchV) : Listed in the 12. BlmSchV (Annex I) under: 1.3.2
Quantity threshold for operational area under § 1 para. 1

- Sentence 1: 200000 kg
- Sentence 2: 500000 kg

Netherlands

Waterbezwaarlijkheid : A (2) - Vergiftig voor in water levende organismen
kan in het aquatische milieu op lange termijn schadelijke effecten veroorzaken

SZW-lijst van kankerverwekkende stoffen : None of the components are listed

SZW-lijst van mutagene stoffen : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : None of the components are listed

Denmark

Class for fire hazard : Class III-1

Store unit : 50 liter

Classification remarks : Flammable according to the Danish Ministry of Justice; Emergency management guidelines for the storage of flammable liquids must be followed

Recommendations Danish Regulation : Young people below the age of 18 years are not allowed to use the product

15.2. Chemical safety assessment

Not applicable

SECTION 16: Other information

Abbreviations and acronyms:

	ABM = Algemene beoordelingsmethodiek
--	--------------------------------------

	SAFETY DATA SHEET	Page : 14 / 15
		Revision nr : 1.0
		Issue date : 16/06/2021
	ANYCUBIC 3D Printing UV Sensitive Resin	Supersedes :

	ADN = Accord Européen relatif au Transport International des Marchandises Dangereuses par voie de Navigation du Rhin ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route CLP = Classification, Labelling and Packaging Regulation according to 1272/2008/EC IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods Code LEL = Lower Explosive Limit/Lower Explosion Limit UEL = Upper Explosion Limit/Upper Explosive Limit REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
	BTT = Breakthrough time (maximum wearing time)
	DMEL = Derived Minimal Effect level
	DNEL = Derived No Effect Level
	EC50 = Median Effective Concentration
	EL50 = Median effective level
	ErC50 = EC50 in terms of reduction of growth rate
	ErL50 = EL50 in terms of reduction of growth rate
	EWG = European waste catalogue
	LC50 = Median lethal concentration
	LD50 = Median lethal dose
	LL50 = Median lethal level
	NA = Not applicable
	NOEC = No observed effect concentration
	NOEL: no-observed-effect level
	NOELR = No observed effect loading rate
	NOAEC = No observed adverse effect concentration
	NOAEL = No observed adverse effect level
	N.O.S. = Not Otherwise Specified
	OEL = Occupational Exposure Limits - Short Term Exposure Limits (STELs)
	PNEC = Predicted No Effect Concentration
	Quantitative structure-activity relationship (QSAR)
	STOT = Specific Target Organ Toxicity
	TWA = time weighted average
	VOC = Volatile organic compounds
	WGK = Wassergefährdungsklasse (Water Hazard Class under German Federal Water Management Act)

Sources of key data used to compile the : ECHA (European Chemicals Agency). LOLI. Supplier information. datasheet

Training advice : Training staff on good practice. Manipulations are to be done only by qualified and authorised persons.

Other information : Classification - Assessment method: CLP Calculation method (Article 9).
Physicochemical hazard assessment: Information given is based on tests on the mixture itself.

Full text of H- and EUH-statements:

Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.

	SAFETY DATA SHEET	Page : 15 / 15
		Revision nr : 1.0
		Issue date : 16/06/2021
	ANYCUBIC 3D Printing UV Sensitive Resin	Supersedes :

H335	May cause respiratory irritation.
H411	Toxic to aquatic life with long lasting effects.

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878
Classification according to Regulation (EC) No. 1272/2008 [CLP]
Labelling according to Regulation (EC) No. 1272/2008 [CLP]

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.