



**1. SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND THE COMPANY/UNDERTAKING**

**1.1 Product identifier**

Product name Engineering LCD Series - Flex 63A Resin  
Product description Photopolymer Resin for 3D-printing (SLA, DLP & LCD)  
Issue date 28-December-2020

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

Identified use Photopolymer is monomer based on acrylic esters for SLA, DLP and/or LCD/MSLA 3D printers with UV-light systems.

Uses advised against -

**1.3 Details of the supplier of the safety data sheet**

FormFutura BV  
Tarweg 3  
6534 AM Nijmegen  
The Netherlands  
Tel.: +31 (0)85 743 4000 (Office hours Mo. - Fr. 09:00 - 17:00 CET)  
e-mail: product.compliance@formfutura.com

**1.4 Emergency Telephone number**

+31 (0)30 274 8888, only for the doctor  
(National PoisonInformation Center Utrecht, The Netherlands)

**2. SECTION 2: HAZARDS IDENTIFICATION**

**2.1 Classification of the substance or mixture**

According to Regulation (EG) No. 1272/2008 [CLP].

Skin Irrit. Cat 2	H315
Eye Irrit. Cat 2	H319
Skin sens. Cat. 1	H317
Aquatic chronic Cat. 2	H411

**2.2 Label elements**



Signal word  
Hazard statement(s)

Warning  
H315: Causes skin irritation.  
H319: Causes serious eye irritation.  
H317: May cause an allergic skin reaction.  
H411: Toxic to aquatic life with long-lasting effects.

Precautionary statement(s)

P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P261: Avoid breathing dust/fumes/gas/mist/vapours/spray.  
P264: Wash thoroughly after handling.  
P272: Contaminated work clothing should not be allowed out of the workplace.  
P273: Avoid release to the environment.  
P302+P352: IF ON SKIN: Wash with plenty of water.





P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.  
P333+P313: If skin irritation or a rash occurs: Get medical advice/attention.  
P337+P313: If eye irritation persists get medical advice/attention.  
P362: Take off contaminated clothing.  
P363: Wash contaminated clothing before reuse.  
P391: Collect spillage.  
P501: Dispose of contents/container in accordance with local/regional/national/international regulation.

## 2.3 Other hazards

Not classified as PBT or vPvB.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1 Substances

This product is a mixture.

### 3.2 Mixtures

Substances in the product which may present a health or environmental hazard, or which have been assigned occupational exposure limits, are detailed below.

According to Regulation (EG) Nr. 1272/2008 [CLP].

Hazardous ingredient(s)	%W/W	EINECS No.	Hazard Class and Category Code(s)	Hazard statement Code(s)
Methyl Acrylate	20 - 40	266-380-7	Skin irrit. Cat. 2 Skin sens. Cat. 1 Aquatic chronic Cat. 2	H315 H317 H411
Unsaturated aliphatic urethane acrylate	20 - 40	Proprietary	STOT single Cat. 3* Skin irrit. Cat. 2 Eye irrit. Cat 2	H335* H315 H319
Phosphine Oxide	<3,0	278-355-8	Skin sens. Cat. 1 Repr. Cat. 2 (fer.) Aquatic chronic Cat. 2	H317 H361f H411
Diisodecyl Phenyl Ester	<0,5	247-098-3	Skin sens. Cat. 1 Aquatic chronic Cat. 3	H317 H412

For full text of H phrases see section 16.

\* %W/W is less than 9% of the determined component with regard to this Hazard Class, Category Code and Hazard Statement. Therefore, the minimum concentration limit for this Hazard Statement has not been achieved.





## SECTION 4: FIRST AID MEASURES

### 4.1 Description of first aid measures

Inhalation	IF INHALED: Move into fresh air and keep at rest. Get medical attention if any discomfort continues.
Skin Contact	IF ON SKIN (or hair): Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention promptly if irritation or other symptoms occur after washing.
Eye Contact	IF IN EYES: Continue to rinse for at least 15 minutes under running water with eyelids held open. Get medical attention if any discomfort continues.
Ingestion	Do not induce vomiting. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Immediately rinse mouth and drink plenty of water. Keep person under observation. If person becomes uncomfortable get medical attention.

### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11. Further important symptoms and effects are so far not known.

### 4.3 Indication of the immediate medical attention and special treatment needed

Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

## SECTION 5: FIRE-FIGHTING MEASURES

### 5.1 Extinguishing media

Suitable Extinguishing Media	Water spray, dry powder, CO <sub>2</sub> .
Unsuitable Extinguishing Media	Water jet.

### 5.2 Special hazards arising from the substance or mixture

Hazards during fire-fighting	Harmful vapours Evolution of fumes/fog
------------------------------	---

High temperatures may cause spontaneous polymerizing reaction generating heat/pressure. Closed containers may rupture or explode during a runaway polymerization. Use a water spray or fog to reduce temperature of containers.

### 5.3 Advice for fire-fighters

Protective equipment Wear a self-contained breathing apparatus and full protective clothing.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures

Use protective gloves, goggles and suitable protective clothing. In case of inadequate ventilation, use respiratory protection. Maximize ventilation after accidental release.

### 6.2 Environmental precautions

Contain contaminated water / firefighting water. Do not discharge into drains/surface waters/groundwater. Avoid release to the environment.

### 6.3 Methods and material for containment and cleaning up

Remove sources of ignition. Absorb with sand or other inert absorbent. Spillage may be stored as chemical waste in approved area. Keep in suitable, closed containers for disposal.





## 6.4 Reference to other sections

See section 8, 13.

## SECTION 7: HANDLING AND STORAGE

### 7.1 Precautions for safe handling

Keep away from heat, sparks and open flame. Use mechanical ventilation in case of handling which causes formation of vapours. Handle and open container with care. Wear full protective clothing for prolonged exposure and/or high concentrations. Take precautionary measures against static discharges.

### 7.2 Conditions for safe storage, including any incompatibilities

Protect from light, including direct sunrays. Container may be filled for only 90%. Keep containers tightly closed, separate from oxidizing agents. Store in original container in a dry, cool and well-ventilated place. Store at temperatures between 5°C and 30°C. Do not expose to temperatures above 50°C for more than 24 hours. High temperatures may cause spontaneous polymerization.

### 7.3 Specific end use(s)

None.

## Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters

Substance	EC No.
Methyl Acrylate (100%)	239-701-3

DNEL (100% component)	Oral	Inhalation	Dermal
Worker – Long Term – Systemic effects	1	3,5 mg/m <sup>3</sup>	83 mg/kg

PNEC (100% component)	
Aquatic Compartment	0,004 mg/l (fresh water)
Terrestrial Compartment	0,019 mg/kg (fresh water)

1 Toxicity: DNEL not established

Substance	EC No.
Unsaturated aliphatic urethane acrylate (100%)	Proprietary

DNEL (100% component)	Oral	Inhalation	Dermal
Worker – Long Term – Systemic effects	1	1	1,04 mg/kg





PNEC (100% component)	
Aquatic Compartment	4,66 ug/l (Fresh water) 0,466 ug/l (Sea water)
Terrestrial Compartment	0,604 mg/kg dry weight

1 Toxicity: DNEL not established

Substance	EC No.
Phosphine Oxide (100%)	278-355-8

DNEL (100% component)	Oral	Inhalation	Dermal
Worker – Long Term – Systemic effects	1	3,5 mg/m3	1,0 mg/kg

PNEC (100% component)	
Aquatic Compartment	0,00353 mg/l (Fresh water) 0,000353 mg/l (Sea water) 0,29 mg/kg dry weight (sediment)
Terrestrial Compartment	0,0557 mg/kg dry weight

1 Toxicity: DNEL not established

Substance	EC No.
Diisodecyl Phenyl Ester(100%)	247-098-3

DNEL (100% component)	Oral	Inhalation	Dermal
Worker – Long Term – Systemic effects	1	70,5 mg/m3	50 mg/kg

PNEC (100% component)	
Aquatic Compartment	Not applicable
Terrestrial Compartment	Not applicable

1 Toxicity: DNEL not established





## 8.2 Exposure controls

### Appropriate engineering controls

Do not eat, drink or smoke at the work place. Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

### Individual protection measures, such as personal protective equipment (PPE)

**Eye/face protection** Wear eye/face protection. Wear approved chemical safety goggles where eyes exposure must be provided. High-efficiency particulate respirator with full face-piece.

**Skin protection** Wear suitable gloves. Butyl and nitrile rubber gloves offer short-term protection. Later surgical gloves offer little protection. Gloves should be stored correctly and changed regularly, especially if excessive exposure has occurred.

**Respiratory protection** Wear suitable respiratory protective equipment if engineering controls are insufficient, or not present, and exposure to levels above the DNEL is likely. A suitable mask with filter type A (EN141 or EN405) may be appropriate.

**Other** Keep working clothes separately. Take off contaminated clothing immediately. Wash soiled clothing before reuse. Keep away from food, drinks and animal feed. Wash thoroughly after handling.

### Environmental exposure controls

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided. Ensure effective control measures when working within the boundaries as specified in section 6.2 of each GES.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

Appearance	Viscous translucent (clear) - different colors possible Ester like
Odour	Not applicable
pH	Not applicable
Melting point	> 200°C
Boiling point	> 150°C
Flash point	
Flammable Limits (lower) (%v/v)	Not applicable
Vapour pressure	-
Solubility (Water)	Not soluble
Solubility	Good solubility with most organic solvents
Auto ignition temperature	Not applicable
Explosive properties	Not applicable
Oxidising properties	Not applicable
Relative density	1.1-1.2 (water = 1)
Viscosity	0.6-0.9 Pa•s

### 9.2 Other information

None

## SECTION 10: STABILITY AND REACTIVITY

### 10.1 Reactivity

See part 10.2.

### 10.2 Chemical stability

Stable under normal temperature conditions. Stable if stored and handles as prescribed/indicated.





**10.3 Possibility of hazardous reactions**

Hazardous polymerization. May polymerize.

**10.4 Conditions to avoid**

Avoid heat, flames and other sources of ignition. Avoid contact with free radical initiators. Avoid contact with isocyanates and oxidizing agents. Avoid contact with vinyl polymerization initiators. Avoid exposure to high temperatures, direct sunlight or ultra violet (UV) radiation.

**10.5 Incompatible materials**

Avoid contact with radical forming initiators, peroxides, strong alkalies or reactive metals to prevent exothermic polymerization.

**10.6 Hazardous Decomposition Product(s)**

With regard to possible decomposition products refer to Section 5. Oxides of carbon.

**SECTION 11: TOXICOLOGICAL INFORMATION**

**11.1 Information on toxicological effects)**

**Stable Acute toxicity:**

Methyl Acrylic (100%)

LD50 acute oral rat	>2000 mg/kg
LD50 acute dermal rabbit	>2000 mg/kg
Skin irritation (rabbit, 24 h, Draize)	Irritating
Eye irritation (rabbit, Draize)	Non-irritating
Inhalation/skin sensitisation (guinea pig, GPMT)	Sensitization
Aspiration Hazard	No aspiration hazard expected

Unsaturated aliphatic urethane acrylate (100%)

LD50 acute oral rat	>2000 mg/kg
LD50 acute dermal rabbit	>2000 mg/kg
Skin irritation (rabbit, 24 h, Draize)	Irritating
Eye irritation (rabbit, Draize)	Irritating
Inhalation/skin sensitisation (guinea pig, GPMT)	Not applicable
Aspiration Hazard	Not applicable

Phosphine Oxide (100%)

LD50 acute dermal rat:	> 2000 mg/kg
Skin irritation (rabbit, 24 h, Draize)	Non-irritant
Eye irritation (rabbit, Draize)	Non-irritant
Skin sensitisation mouse LLNA (OESO 429)	Sensitizing
Aspiration Hazard	No aspiration hazard expected
Chronic toxicity (animal studies)	May cause damage after repeated ingestion of high doses
Reproductive toxicity (animal studies)	Suggest a fertility impairing effect

Diisodecyl Phenyl Ester (100%)

LD50 acute oral rat	>5000 mg/kg
LD50 acute dermal rabbit	>2000 mg/kg
Skin irritation (rabbit, 24 h, Draize)	Not classified based on available data
Eye irritation (rabbit, Draize)	Not classified based on available data
Inhalation/skin sensitisation (guinea pig, GPMT)	May cause an allergic skin reaction
Aspiration Hazard	Not classified based on available data
Reproductive toxicity (animal studies)	Not classified based on available data





## SECTION 12: ECOLOGICAL INFORMATION

### 12.1 Toxicity

#### Methyl Acrylate (100%)

Toxicity to fish (mg/l)	LC50 (96 h) (Oncorhynchus mykiss) (OESO 203)	4 mg/L
Aquatic invertebrates (mg/l)	EC50 (72 h) (Daphnia magna) (OESO 202)	20 mg/L
Aquatic plants (mg/l)	EC50 (72 h) (Desmodesmus subspicatus) (OECD 201)	18.8 mg/L
	EC10 (72 h) (Desmodesmus subspicatus)(OESO 201)	1.9 mg/L
Microorganisms (mg/l)	NOEC (28 d) (Activated sludge) (DEV L8)	NB

#### Unsaturated aliphatic urethane acrylate (100%)

Toxicity to fish (mg/l)	LC50 (96 h) (Danio rerio) (OESO 203)	n/a
Aquatic invertebrates (mg/l)	NOEC (21 d) (Daphnia magna) (OESO 202)	n/a
Aquatic plants (mg/l)	EC50 (72 h) (Pseudokirchnerella subcapitata) (OESO 201)	n/a

#### Phosphine Oxide (100%)

Toxicity to fish (mg/l)	LC50 (96 h) (Brachydanio rerio) (OESO 203)	>90
Aquatic invertebrates (mg/l)	EC50 (48 h) (Daphnia magna) (OECD 202)	>1175
Aquatic plants (mg/l)	EC50 (72 h) (Desmodesmus subspicatus) (OECD 201)	>260
Microorganisms (mg/l)	EC50 (3 h) (Activated sludge) (DEC L8)	>100

#### Diisodecyl Phenyl Ester (100%)

Harmful to aquatic life with long lasting effects.

Aquatic plants (mg/l)	EC50 (72 h) (Selenastrum capricornutum) (OESO 201)	45
	NOEC (72 h) (Selenastrum capricornutum) (OESO 201)	>100

### 12.2 Persistence and degradability

#### Methyl Acrylate (100%)

No data available

#### Unsaturated aliphatic urethane acrylate (100%)

No data available

#### Phosphine Oxide (100%)

Poorly biodegradable. Not readily biodegradable (by OECD criteria)

Elimination information:

< 20% BOD of the ThOD (28 d) (OECD 301 F) (activated sludge)

#### Diisodecyl Phenyl Ester (100%)

Biodegradable.

### 12.3 Bioaccumulative potential

#### Methyl Acrylate (100%)

No data available

#### Unsaturated aliphatic urethane acrylate (100%)

No data available

#### Phosphine Oxide (100%)

Does not significantly accumulate in organisms

Bioconcentration factor: 23 – 55 (56 d), Cyprinus carpio (measured): does not significantly accumulate in organisms.

#### Diisodecyl Phenyl Ester (100%)

Partition coefficient, n-octanol/water (log Pow): 8,52 - 12,31



**12.4 Mobility in soil**Methyl Acrylate (100%)

No data available

Unsaturated aliphatic urethane acrylate (100%)

No data available

Phosphine Oxide (100%)

The substance will not evaporate into the atmosphere from the water surface.

Adsorption to solid soil phase is not expected.

Diisodecyl Phenyl Ester (100%)

No further relevant information available.

**12.5 Results of PBT and vPvB assessment**Methacrylic Oligomer (100%)

PBT: no

vPvB: no

Unsaturated aliphatic urethane acrylate (100%)

No data available

Phosphine Oxide (100%)

PBT: no

vPvB: no

Diisodecyl Phenyl Ester (100%)

No data available

**12.6 Other adverse effects**Methyl Acrylate (100%)

No data available

Unsaturated aliphatic urethane acrylate (100%)

No data available

Phosphine Oxide (100%)

Not applicable.


Diisodecyl Phenyl Ester (100%)

No data available.

**SECTION 13: DISPOSAL CONSIDERATIONS****13.1 Waste treatment methods**

Do not discharge into drains/surface waters/groundwater. Dispose of in accordance with national, state and local regulations. Incinerate under approved controlled conditions, using incinerators for the disposal for organic chemicals. Decontaminate empty drums before recycling.



**SECTION 14: TRANSPORT INFORMATION****Additional information**

Products are transported by FormFutura in sizes ≤5L or ≤5kg. The environmentally hazardous substance mark is not required when transported in sizes of ≤5L or ≤5kg. The marine pollutant mark is not required when transported in sizes of ≤5L or ≤5kg. More information about Special Provisions: see Section 14.6 'Further information'.

**14.1 UN-Nummer**

ADR/RID: 3082

IMDG: 3082

IATA: 3082

**14.2 UN Proper Shipping Name**

ADR/RID: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

IMDG: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

IATA: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

**14.3 Transport hazard class(es)**

ADR/RID: 9

IMDG: 9

IATA: 9

**14.4 Packing group**

ADR/RID: III

IMDG: III

IATA: III

**14.5 Environmental hazards**

ADR/RID: yes

IMDG Marine pollutant: yes

IATA: yes

**14.6 Special precautions for user****Further information**

EHS-Mark required (ADR 2.2.9.1.10, IMDG code 2.10.3) for single packagings and combination packagings containing inner packagings with Dangerous Goods > 5L for liquids or > 5kg for solids.

Exception - Special Provisions

ADR/RID: Special Provisions 274, 335, 601, 375.

NOT RESTRICTED as per Special Provisions 375. The provided packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

IMDG: Special Provisions 274, 335, 969.

NOT RESTRICTED as per 2.10.2.7. The provided packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

IATA: Special Provisions A97, A158, A197.

NOT RESTRICTED as per Special Provisions A197. The provided packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.


**SECTION 15: REGULATORY INFORMATION****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

If information other than the information in relation to safety, health and environmental regulations / legislation what is mentioned elsewhere in this Safety Data Sheet is required, please use the information listed in Section 1 to inquire whether that specific information is available. Related information about the separate components in the mixture can be accessed the same way.

**15.2 Chemical Safety Assessment**

A Chemical Safety Assessment has been carried out for Diisodecyl Phenyl Ester (100%).



**SECTION 16: OTHER INFORMATION**

This Safety Data Sheet was prepared in accordance with EC Regulation (EC) No. 453/2010.

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process unless specified in the text.

**LEGEND**

Note: Not all of the following are necessarily contained in this Safety Data Sheet:

IOELV:	Indicative Occupational Exposure Limit Value.
WEL:	Workplace Exposure Limit.
Sen:	Capable of causing respiratory sensitization.
Carc:	Capable of causing cancer and/or heritable genetic damage.
COM:	The company aims to control exposure in its workplace to this limit.
LTEL:	Long Term Exposure Limit.
STEL:	Short Term Exposure Limit.
TWA:	Time Weighted Average.
STOT SE:	Specific Target Organ Toxicity – Single Exposure.
Repr.:	Reproductive toxicity.
Aquatisch acute/chronic:	Hazardous to the aquatic environment.

Full text of H/P/R phrases

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H335: May cause respiratory irritation.

H361f: Suspected of damaging fertility.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long-lasting effects.

H411: Toxic to aquatic life with long-lasting effects.

H412: Harmful to aquatic life with long lasting effects.

H413: May cause long-lasting harmful effects to aquatic life.

P261: Avoid breathing vapours.

P264: Wash thoroughly after handling.

P272: Contaminated work clothing should not be allowed out of the workplace.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302 + P352: IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.

P333 + P313: If skin irritation or rash occurs: Get medical advice/attention.

P337+P313: If eye irritation persists get medical advice/attention.

P362: Take off contaminated clothing.

P363: Wash contaminated clothing before reuse.

P362 + P364: Take off contaminated clothing and wash it before reuse.

P391: Collect spillage.

P501: Dispose of contents/container to hazardous waste in accordance with local, state or national legislation. Incinerate under approved controlled conditions, using incinerators suitable for the disposal of flammable organics.





## Further information

Copyright 2020 FormFutura BV. License granted to make unlimited paper copies for internal use only.

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide.

The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. FormFutura BV and its affiliates shall not be held liable for any damage resulting from handling or from contact with the above product.

See [www.formfutura.com](http://www.formfutura.com) for additional terms and conditions of sale.

