



1. SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND THE COMPANY/UNDERTAKING

1.1	Product identifier Product name Product description Issue date	Engineering SLA Series - Heavy Duty Resin - Grey Photopolymer Resin for 3D-printing (SLA, DLP & LCD/MSLA). 21-December-2020
1.2	Relevant identified uses of t Identified use	the substance or mixture and uses advised against Photopolymer is monomer based on acrylic esters for SLA, DLP & LCD/MSLA 3D printers with UV-light systems.
	Uses advised against	-
1.3	Details of the supplier of the	e safety data sheet FormFutura BV Tarweweg 3 6534 AM Nijmegen The Netherlands Tel.: +31 (0)85 743 4000 e-mail: product.compliance@formfutura.com
1.4	Emergency Telephone num	ber

+31 (0)30 274 8888, only for the doctor (National Poison Information Center Utrecht, The Netherlands)

2. SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

According to Regulation (EG) No. 1272/2008 [CLP].	
Skin irrit. Cat. 2	H315
Skin sens. Cat. 1	H317
Eye irrit. Cat. 1	H319
Aquatic chronic Cat. 4	H413

2.2 Label elements

Ô



Signal word Hazerd statement(s)	Warning H315: Causes skin irritation. H317: May cause an allergic skin reaction. H319: Causes serious eye irritation. H413: May cause long-lasting harmful effects to aquatic life.
Precautionary statement(s)	 P280: Wear protective gloves/protective clothing/eye protection/face protection. P261: Avoid breathing dust/fumes/gas/mist/vapours/spray. P264: Wash thoroughly after handling. P272: Contaminated work clothing should not be allowed out of the workplace. P273: Avoid release to the environment. P302+P352: IF ON SKIN: Wash with plenty of water.

FormFutura B.V. - Tarweweg 3 - 6534 AM - Nijmegen - The Netherlands - Phone: +31 (0)85 743 4000 - Email: info@formfutura.com - www.formfutura.com Dutch Business Registration Number: 69099502 - VAT/BTW Number: NL857733709B01 - EORI Number: NL857733709 - D-U-N-S Number: 490546732





P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. P332+P313: If skin irritation occurs: Get medical advice/attention. P333+P313: If skin irritation or a rash occurs: Get medical advice/attention. P337+P313: If eye irritation persists: Get medical advice/ attention. P362+P364: Take off contaminated clothing and wash it before reuse. P501: Dispose of contents/container in accordance with local/regional/national/ international regulation.

2.3 Other hazards

Not classified as PBT or vPvB.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

This product is a mixture.

3.2 Mixtures

Substances in the product which may present a health or environmental hazard, or which have been assigned occupational exposure limits, are detailed below.

Hazardous ingredient(s)	%W/W	EINECS No.	Hazard Class and Category Code(s)	Hazard statement Code(s)
Methacrylic Oligomer	65 - 85	Proprietary	Skin sens. Cat 1	H317
Glycol Methacrylate	10 - 30	212-782-2	Skin irrit. Cat. 2 Skin sens. Cat. 1 Eye irrit. Cat. 2	H315 H317 H319
Benzoxazole	<0,4	230-426-4	Aquatic chronic Cat 4	H413
Phosphine Oxide	<2	278-355-8	Skin sens. Cat 1 Repr. Cat 2 (fer.) Aquatic chronic Cat 2	H317 H361f H411

According to Regulation (EG) Nr. 1272/2008 [CLP].

For full text of H phrases see section 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

Description of instant measuresInhalationIF INHALED: Move into fresh air and keep at rest. Get medical attention if any discomfort
continues.Skin ContactIF ON SKIN (or hair): Remove contaminated clothing immediately and wash skin with soap and
water. Get medical attention promptly if irritation or other symptoms occur after washing.Eye ContactIF IN EYES: Continue to rinse for at least 15 minutes under running water with eyelids held
open. Get medical attention.IngestionDo not induce vomiting. Never induce vomiting or give anything by mouth if the victim is
unconscious or having convulsions. Immediately rinse mouth and drink plenty of water. Keep

FormFutura B.V. - Tarweweg 3 - 6534 AM - Nijmegen - The Netherlands - Phone: +31 (0)85 743 4000 - Email: info@formfutura.com - www.formfutura.com Dutch Business Registration Number: 69099502 - VAT/BTW Number: NL857733709B01 - EORI Number: NL857733709 - D-U-N-S Number: 490546732

person under observation. If person becomes uncomfortable get medical attention.





4.2 Most important symptoms and effects, both acute and delayed The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11. Further important symptoms and effects are so far not known.

4.3 Indication of the immediate medical attention and special treatment needed Note to physician Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

SECTION 5: FIRE-FIGHTING MEASURES

- 5.1Extinguishing mediaSuitable Extinguishing MediaWater spray, dry powder, CO2.Unsuitable Extinguishing MediaWater jet.
- 5.2 Special hazards arising from the substance or mixture
 Hazards during fire-fighting
 Harmful vapours
 Evolution of fumes/fog

 High temperatures may cause spontaneous polymerizing reaction generating heat/pressure. Closed containers may rupture or explode during a runaway polymerization. Use a water spray or fog to reduce temperature of containers.
- 5.3Advice for fire-fightersProtective equipmentWear a self-contained breathing apparatus and full protective clothing.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures Use protective gloves, goggles and suitable protective clothing. In case of inadequate ventilation, use respiratory protection. Maximize ventilation after accidental release.

6.2 Environmental precautions

Contain contaminated water / firefighting water. Do not discharge into drains/surface waters/groundwater. Avoid release to the environment.

- 6.3 Methods and material for containment and cleaning up Remove sources of ignition. Absorb with sand or other inert absorbent. Spillage may be stored as chemical waste in approved area.
- 6.4 Reference to other sections

See section 8, 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Keep away from heat, sparks and open flame. Use mechanical ventilation in case of handling which causes formation of vapours. Handle and open container with care. Wear full protective clothing for prolonged exposure and/or high concentrations. Take precautionary measures against static discharges.

7.2 Conditions for safe storage, including any incompatibilities

Protect from light, including direct sunrays. Container may be filled for only 90%. Keep containers tightly closed, separate from oxidizing agents. Store in original container in a dry, cool and well-ventilated place. Store at temperatures between 5°C and 30°C. Do not expose to temperatures above 50°C for more than 24 hours. High temperatures may cause spontaneous polymerization.

`b)





Specific end use(s) 7.3

None.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 **Control parameters**

	0	Inholot	Demad	
Methacrylic Oligomer (100%)	Proprietary			
Substance	EC No.			

DNEL (100% component)	Oral	Inhalation	Dermal
Worker – Long Term – Systemic effects	1	1	1

PNEC (100% component)	
Aquatic Compartment	Not applicable
Terrestrial Compartment	Not applicable

1 Toxicity: DNEL not established

Substance	EC No.		LTEL mg/m ³ (8 h TWA)
Glycol Methacrylate (100%)	212-782-2	0,05	0,24

DNEL (100% component)	Oral	Inhalation	Dermal
Worker – Long Term – Systemic effects	1	4,9 mg/m3	1,3 mg/kg

PNEC (100% component)	
Aquatic Compartment	10 mg/l (Fresh water) 0,482 mg/l (Sea water) 3,79 mg/kg dry weight (sediment)
Terrestrial Compartment	0,476 mg/kg dry weight

1 Toxicity: DNEL not established

Substance	EC No.	
Phosphine Oxide (100%)	278-355-8	

DNEL (100% component)	Oral	Inhalation	Dermal
Worker – Long Term – Systemic effects	1	3,5 mg/m3	1,0 mg/kg



PNEC (100% component)	
	0,00353 mg/l (Fresh water) 0,000353 mg/l (Sea water) 0,29 mg/kg dry weight (sediment)
Terrestrial Compartment	0,0557 mg/kg dry weight

1 Toxicity: DNEL not established

Substance	EC No.	
Benzoxazole (100%)	230-426-4	

DNEL (100% component)	Oral	Inhalation	Dermal
Worker – Long Term – Systemic effects	1	1	1

PNEC (100% component)	
Aquatic Compartment	Not applicable
Terrestrial Compartment	Not applicable

1 Toxicity: DNEL not established

8.2 Exposure controls

Appropriate engineering controls

Do not eat, drink or smoke at the work place. Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

Individual protection measures, s Eye/face protection	<u>uch as personal protective equipment (PPE)</u> Wear eye/face protection. Wear approved chemical safety goggles where eyes exposure must be provided. High-efficiency particulate respirator with full face-piece.
Skin protection	Wear suitable gloves. Butyl and nitrile rubber gloves offer short-term protection. Later surgical gloves offer little protection. Gloves should be stored correctly and changed regularly, especially if excessive exposure has occurred.
Respiratory protection	Wear suitable respiratory protective equipment if engineering controls are insufficient, or not present, and exposure to levels above the DNEL is likely. A suitable mask with filter type A (EN141 or EN405) may be appropriate.
Other	Keep working clothes separately. Take off contaminated clothing immediately. Wash soiled clothing before reuse. Keep away from food, drinks and animal feed. Wash hands thoroughly after handling.

Environmental exposure controls

Ô

Ensure effective control measures when working within the boundaries as specified in section 6.2 of each GES.







SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance Odour pH Melting point Flash point Flash point Flammable Limits (lower) (%v/v) Vapour pressure Solubility (Water) Solubility Auto ignition temperature Explosive properties Oxidising properties Relative density Viscosity	Viscous liquid - grey (but different colors possible) Ester like Not applicable > 200°C > 150°C Not applicable - Not soluble Good solubility with most organic solvents 380°C Not applicable Not applicable 1.1-1.2 (water = 1) 0.6-1.4 Pa•s

9.2 Other information

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

See part 10.2.

- **10.2** Chemical stability Stable under normal temperature conditions. Stable if stored and handles as prescribed/indicated.
- 10.3 Possibility of hazardous reactions

Hazardous polymerization. May polymerize.

10.4 Conditions to avoid

Avoid heat, flames and other sources of ignition. Avoid contact with free radical initiators. Avoid contact with isocyanates and oxidizing agents. Avoid contact with vinyl polymerization initiators. Avoid exposure to high temperatures, direct sunlight or ultra violet (UV) radiation.

10.5 Incompatible materials

Avoid contact with radical forming initiators, peroxides, strong alkalies or reactive metals to prevent exothermic polymerization.

10.6 Hazardous Decomposition Product(s)

With regard to possible decomposition products refer to Section 5: Oxides of carbon.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects Stable Acute toxicity:

Methacrylic Oligomer (100%) LD50 acute Skin irritation Eye irritation Inhalation/skin sensitisation Aspiration Hazard

No information available No information available No information available No information available No aspiration hazard expected

None





<u>Glycol Methacrylate (100%)</u> LD50 acute oral rat LD50 acute dermal rabbit Skin irritation (rabbit, 24 h, Draize) Eye irritation (rabbit, Draize) Inhalation (guinea pig, GPMT) Aspiration Hazard Chronic toxicity oral rat (OESO 422) Reproductive toxicity (animal studies)

Phosphine Oxide (100%) LD50 acute dermal rat: Skin irritation (rabbit, 24 h, Draize) Eye irritation (rabbit, Draize) Skin sensitation mouse LLNA (OESO 429) Aspiration Hazard Chronic toxicity (animal studies) Reproductive toxicity (animal studies)

Benzoxale (100%) Skin irriation Skin sensitation

> 5000 mg/kg > 5000 mg/kg non-irritant Irritating Sensitizing no aspiration hazard expected > 100 mg/kg No suspicion of a toxic effect on reproduction

> 2000 mg/kg
 Non-irritant
 Non-irritant
 Sensitizing
 No aspiration hazard expected
 May cause damage after repeated ingestion of high doses
 Suggest a fertility impairing effect

Non-irritant No sensitization

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

2.1	TOXICITY		
	Methacrylic Oligomer (100%)		
	Toxicity to fish (mg/l)	LL50 (96 h) (Oncorhynchus mykiss) (OESO 203)	No data available
	Aquatic invertebrates (mg/l)	EL50 (72 h) (Daphnia magna) (OESO 202)	No data available
	Aquatic plants (mg/l)	EL50 (72 h) (Pseudokirchneriella subcapitata) (OECD 201) NOEC (72 h) (Selenastrum capricornutum) (OESO 201)	No data available No data available
	Microorganisms (mg/l)	NOEC (28 d) (Activated suldge) (DEV L8)	No data available
	Glycol Methacrylate (100%)		
	Toxicity to fish (mg/l)	LC50 (96 h) (Oryzias latipes) (OESO 203)	>100
	Aquatic invertebrates (mg/l)	NOEC (21 d) (Daphnia magna) (OESO 202)	24,1
		EC50 (48 h) (Daphnia magna) (OESO 202)	380
	Aquatic plants (mg/l)	EC50 (72 h) (Selenastrum capricornutum) (OESO 201)	836
		NOEC (72 h) (Selenastrum capricornutum) (OESO 201)	400
	Microorganisms (mg/l)	EC50 (16 h) (Pseudomonas fluorescens) (DEV L8)	>3000
	Phosphine Oxide (100%)		
	Toxicity to fish (mg/l)	LC50 (96 h) (Brachydanio rerio) (OESO 203)	>90
	Aquatic invertebrates (mg/l)	EC50 (48 h) (Daphnia magna) (OECD 202)	>1175
	Aquatic plants (mg/l)	EC50 (72 h) (Desmodesmus subspicatus) (OECD 201)	>260
	Microorganisms (mg/l)	EC50 (3 h) (Activated sludge) (DEC L8)	>100
	Benzoxazole (100%)		
	Toxicity to fish (mg/l)	LC50 (96 h) (Brachydanio rerio) (OESO 203)	>100

FormFutura B.V. - Tarweweg 3 - 6534 AM - Nijmegen - The Netherlands - Phone: +31 (0)85 743 4000 - Email: info@formfutura.com - www.formfutura.com Dutch Business Registration Number: 69099502 - VAT/BTW Number: NL857733709B01 - EORI Number: NL857733709 - D-U-N-S Number: 490546732





12.2 Persistence and degradability

Methacrylic Oligomer (100%) No data available

<u>Glycol Methacrylate (100%)</u> Easy biodegradable. Elimination information: 84% DOC reduction (28 d) (OESO 301 D)

Phosphine Oxide (100%) Poorly biodegradable. Not readily biodegradable (by OECD criteria) Elimination information: < 20% BOD of the ThOD (28 d) (OECD 301 F) (activated sludge)

Benzoxazole (100%) No data available.

12.3 Bioaccumulative potential

Methacrylic Oligomer (100%) No data available.

<u>Glycol Methacrylate (100%)</u> Accumulation in organisms is not to be expected.

Phosphine Oxide (100%) Does not significantly accumulate in organisms. Bioconcentration factor: 23 – 55 (56 d), Cyprinus carpio (measured): does not significantly accumulate in organisms.

Benzoxazole (100%) No data available.

12.4 Mobility in soil

Methacrylic Oligomer (100%) No data available

Glycol Methacrylate (100%) The substance will not evaporate into the atmosphere from the water surface. Adsorption to solid soil phase is not expected.

<u>Phosphine Oxide (100%)</u> The substance will not evaporate into the atmosphere from the water surface. Adsorption to solid soil phase is not expected.

Benzoxazole (100%) No data available.

12.5 Results of PBT and vPvB assessment

Methacrylic Oligomer (100%) PBT: no vPvB: no

<u>Glycol Methacrylate (100%)</u> PBT: no vPvB: no







Phosphine Oxide (100%) PBT: no vPvB: no

Benzoxazole (100%) PBT: no vPvB: no

12.6 Other adverse effects

Methacrylic Oligomer (100%) Not applicable.

<u>Glycol Methacrylate (100%)</u> Do not allow to enter soil, waterways or waste water channels.

Phosphine Oxide (100%) Not applicable

Benzoxazole (100%) Not applicable

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Do not discharge into drains/surface waters/groundwater. Dispose of in accordance with national, state and local regulations. Incinerate under approved controlled conditions, using incinerators for the disposal for organic chemicals. Decontaminate empty drums before recycling.

SECTION 14: TRANSPORT INFORMATION

- **14.1 UN-Nummer** Not classified as a dangerous good under transport regulations.
- **14.2 UN Proper Shipping Name** Not applicable.
- **14.3 Transport hazard class(es)** Not applicable.
- **14.4 Packing group** Not applicable.

Ó

- **14.5** Environmental hazards Toxic to aquatic life with long lasting effects.
- 14.6 Special precautions for user
- 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code





SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture If information other than the information in relation to safety, health and environmental regulations / legislation what is mentioned elsewhere in this Safety Data Sheet is required, please use the information listed in Section 1 to inquire whether that specific information is available. Related information about the separate components in the mixture can be accessed the same way.

15.2 Chemical Safety Assessment

A Chemical Safety Assessment has been carried out for the following individual component (100%): Glycol Methacrylate.

SECTION 16: OTHER INFORMATION

This Safety Data Sheet was prepared in accordance with EC Regulation (EC) No. 453/2010.

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process unless specified in the text.

LEGEND

Note: Not all of the following are necessarily contained in this Safety Data Sheet:		
WEL:	Workplace Exposure Limit.	
Sen:	Capable of causing respiratory sensitization.	
Sk:	Can be absorbed through skin.	
Carc:	Capable of causing cancer and/or heritable genetic damage. Long	
LTEL:	Term Exposure Limit.	
STEL:	Short Term Exposure Limit.	
TWA:	Time Weighted Average.	
STOT SE:	Specific Target Organ Toxicity – Single Exposure.	
Repr.:	Reproductive toxicity.	
Aquatisch acute/chronic:	Hazardous to the aquatic environment.	

Full text of H/P/R phrases

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H361f: Suspected of damaging fertility.

H411: Toxic to aquatic life with long-lasting effects.

H413: May cause long-lasting harmful effects to aquatic life.

P261: Avoid breathing vapours.
P264: Wash (hands and exposed skin) thoroughly after handling.
P272: Contaminated work clothing should not be allowed out of the workplace.
P273: Avoid release to the environment.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P302 + P352: IF ON SKIN: Wash with plenty of soap and water.
P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.
P332 + P313: If skin irritation occurs: Get medical advice/attention.
P333 + P313: If skin irritation or rash occurs: Get medical advice/attention.
P362 + P364: Take off contaminated clothing and wash it before reuse.
P501: Dispose of contents/container to hazardous waste in accordance with local, state or national legislation. Incinerate under approved controlled conditions, using incinerators suitable for the disposal of flammable organics.

 $\left(\right)$